Press release



September 2020

Press contact: Tim Bowern 020 8654 8945 07854 966 071 tim@hashstar.co.uk www.wharfedale.co.uk +44 (0)1480 447700



Above Wharfedale Diamond 12 Series speakers in walnut finish

Only a Diamond cuts to the heart of the music

Wharfedale's iconic Diamond lineage of high-performance, high-value speakers sparkles brighter than ever with the all-new Diamond 12 Series

Cambridgeshire, England – Since 1982, Wharfedale's famous Diamond speakers have served as the classic entry point to true high-fidelity sound, their exceptional sonic value for money earning numerous 'product of the year' accolades in the UK and around the world. This autumn, with the introduction of the all-new Diamond 12 Series, Wharfedale once again raises the bar for affordable, high-performance loudspeakers.

To develop the new range, Wharfedale has collaborated with world-renowned speaker designer Karl-Heinz Fink for the first time. Fink's track record of delivering class-leading sound from modestly priced speakers is exceptional and with the Diamond 12 Series, he and Wharfedale's team of acoustic engineers have achieved a new entry-level benchmark.

Wharfedale determined that the Diamond 12 Series should be an opportunity to start afresh. A challenge was issued to Mr Fink: how much sonic performance can you wring from a range of speakers at classic Diamond price points? And so, he and Wharfedale's team set to work, delivering clean-sheet designs without a single element unaltered from the outgoing – and more costly – Diamond 11 Series.

With recommend retail prices starting at £199, the new range comprises three standmount speakers, two floorstanding models and a centre speaker for home cinema configurations.

Wharfedale Diamond 12 Series				
Standmount speakers	Floorstanding speakers	Home cinema centre speaker		
Diamond 12.0 – £199 per pair	Diamond 12.3 – £499 per pair	Diamond 12.C – £229		
Diamond 12.1 – £249 per pair	Diamond 12.4 – £699 per pair			
Diamond 12.2 – £299 per pair		•		



Left Wharfedale Diamond 12.4 floorstanding speakers in walnut finish

Klarity™ – the difference is clear

Since the Diamond 8 Series in 2001, Wharfedale has made the mid/bass cones for every Diamond generation from Kevlar. 19 years and many award-wining ranges later, Wharfedale has developed a new composite called Klarity™.

The chief ingredient of Klarity™ is polypropylene, a material that has been used to make speaker cones since the BBC researched its use for this purpose in the 1970s. Polypropylene cones are renowned for their characteristically low distortion and controlled 'breakup', as well as their resistance to moisture in the air. They also have a reputation in some quarters for sounding a little 'unexciting' – a perception that is largely the result of mediocre engineering. When designed and implemented optimally, polypropylene cones can sound enthralling.

To make Klarity[™], Wharfedale adds mica to the formulation. This increases stiffness compared to polypropylene alone, reducing flexing and enabling a lightweight cone with high rigidity, low colouration and lightning-fast response – ideal characteristics to deliver both accuracy and excitement.


Mid/bass drivers - cone surround, magnet and voice coil

Polypropylene speaker cones are often combined with high-damping surrounds to achieve a smooth response curve. However, the hysteresis of these surrounds can restrict dynamics and make bass sound somewhat 'soft'.

For the Diamond 12 Series, the aim was to combine the Klarity[™] cone with a low-damping surround, thereby achieving both low colouration and expressive dynamics. This was not a simple task but, by simulating many different cone shapes and adding ribs to provide further stiffening, a flat response curve was achieved without resorting to a high-damping surround, thereby striking the ideal balance.

The Klarity™ diaphragms are driven by a substantial, precision-made magnet system with an aluminium compensation ring to minimise the effect of variations in inductance as the voice coil travels. This contributes to an absence of distortion and intermodulation generated by the motor system.

The voice coil is wound on a high-power epoxy/glass fibre bobbin – highly unusual in speakers at this price level. This has the advantage of not adding eddy currents and delivering greater power handling than an aluminium bobbin, whilst also being much stiffer than the Kapton type.



Left Diamond 12 mid/bass driver assembly, featuring a Klarity[™] cone with low-damping surround

Treble unit and crossover

The Diamond 12 Series' treble unit sports a 25mm dome made from a woven polyester film with a high-loss coating to deliver open and smoothly extended high frequencies. The magnet system and the front plate have been optimised for wide dispersion and uncompressed behaviour. The front plate is flat and exposes the dome as much as possible, with a short duct to balance the acoustic load and improve the SPL (sound pressure level) measurement.

The treble unit combines seamlessly with the mid/bass driver via a crossover network using an acoustic LKR 24dB topology. This includes air core inductors of the type more commonly found in high-end speakers, selected because they produce the lowest distortion of all inductor types. As the resistance of

the coil is higher than a standard laminated steel or ferrite core inductor, the magnetic structure of the mid/bass driver has been modified to compensate, resulting in fast, clean bass with no distortion from the inductor.




Left Diamond 12 treble driver assembly, featuring woven polyester film dome


Cabinet construction

The cabinet is a critical part of any high-performance loudspeaker. At entry-level price points, corners are often cut to constrain cost, but this is a mistake; no matter how good the drive units, their performance will be wasted if the cabinet's construction is suboptimal. For this reason, Diamond 12 Series speakers feature cabinets constructed with a level of sophistication usually reserved for much more expensive designs.

The rear-ported enclosure of each model is precisely sized so that the internal volume works in harmony with the drive unit system to deliver the desired sonic result. The cabinet walls are made from sections of wood fibre board of varying thickness, constructed in such a way as to subdue the identifiable characteristics of the cabinet's 'sound' and ensure the drivers' output remains unsullied. The resonant properties of each element – even the glue – were considered to determine the ideal combination of materials and placement.

Inside the cabinet, Intelligent Spot Bracing connects opposing walls with a specific form of wood brace to achieve optimal reduction of cabinet resonance. These braces are precisely modelled by computer simulation to improve upon the commonplace 'figure of eight' brace, which can have the effect of transferring resonance from one wall to another.





Left These images reveal cabinet resonance before and after Intelligent Spot Bracing is applied – the 'hotter' the colour, the greater the resonance

Diamond 12: a music lover's best friend - available from October

A bestseller in every Wharfedale Diamond line-up from the last two decades is the '.1' model – a classically sized 'bookshelf' speaker evolved over many generations from the original Diamond blueprint. The Diamond 12.1 continues this tradition and is the first Diamond 12 model to arrive – available from 1 October.

For many decades, Wharfedale has been famous for fusing even-handed neutrality and transparency with captivating clarity and expression, and the Wharfedale Diamond 12.1 embodies that sonic goal. This is a 'budget' loudspeaker that captures the spirit of the music, whatever you play – from rock to classical, jazz to electronica – whilst accurately conveying the recording as all great 'hi-fi' should.

The other Diamond 12 models are set to join the 12.1 in November, each one delivering the same adroit balance of subtlety and expression, with increasing levels of sonic power and scale as one moves up the range. All models are offered in a choice of black, white, walnut or light oak.

For high-performance sound at entry-level prices, only a Diamond cuts to the heart of the music – and Wharfedale's Diamond 12 Series speakers are the best 'budget' gems yet.



Specifications	Diamond 12.0	Diamond 12.1	Diamond 12.2
Speaker type	2-way standmount speaker	2-way standmount speaker	2-way standmount speaker
Enclosure type	Bass reflex	Bass reflex	Bass reflex
Treble driver	25mm textile dome	25mm textile dome	25mm textile dome
Mid/bass driver	100mm Klarity™ composite	130mm Klarity™ composite	150mm Klarity™ composite
Dedicated bass driver	N/A	N/A	N/A
Sensitivity (2.83v @ 1m)	87dB	88dB	88dB
Recommended amp power	20-60W	20-100W	20-120W
Peak SPL	95dB	96dB	96dB
Nominal impedance	8Ω compatible	8Ω compatible	8Ω compatible
Minimum impedance	4Ω	4Ω	4Ω
Frequency response (+/-3dB)	70Hz-20kHz	65Hz-20kHz	50Hz-20kHz
Bass extension (-6dB)	65Hz	60Hz	43Hz
Crossover frequency	2.7kHz	2.6kHz	2kHz
Dimensions (HxWxD)	265x160x200mm	312x180x250mm	335x200x285mm
Weight (each)	5.1kg	6.8kg	8.2kg
1			
Specifications	Diamond 12.3	Diamond 12.4	Diamond 12.C
Specifications Speaker type	Diamond 12.3 2.5-way floorstanding speaker	Diamond 12.4 2.5-way floorstanding speaker	Diamond 12.C 2-way centre speaker
Speaker type	2.5-way floorstanding speaker	2.5-way floorstanding speaker	2-way centre speaker
Speaker type Enclosure type	2.5-way floorstanding speaker Bass reflex	2.5-way floorstanding speaker Bass reflex	2-way centre speaker Closed-box system
Speaker type Enclosure type Treble driver	2.5-way floorstanding speaker Bass reflex 25mm textile dome	2.5-way floorstanding speaker Bass reflex 25mm textile dome	2-way centre speaker Closed-box system 25mm textile dome
Speaker type Enclosure type Treble driver Mid/bass driver	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2)
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m)	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power Peak SPL	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W 102dB	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W 102dB	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W 96dB
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power Peak SPL Nominal impedance	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W 102dB 8Ω compatible	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W 102dB 8Ω compatible	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W 96dB 8Ω compatible
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power Peak SPL Nominal impedance Minimum impedance	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W 102dB 8Ω compatible 5Ω	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W 102dB 8Ω compatible 5Ω	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W 96dB 8Ω compatible 4Ω
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power Peak SPL Nominal impedance Minimum impedance Frequency response (+/-3dB)	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W 102dB 8Ω compatible 5Ω 45Hz-20kHz	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W 102dB 8Ω compatible 5Ω 40Hz-20kHz	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W 96dB 8Ω compatible 4Ω 90Hz-20kHz
Speaker type Enclosure type Treble driver Mid/bass driver Dedicated bass driver Sensitivity (2.83v @ 1m) Recommended amp power Peak SPL Nominal impedance Minimum impedance Frequency response (+/-3dB) Bass extension (-6dB)	2.5-way floorstanding speaker Bass reflex 25mm textile dome 130mm Klarity™ composite 130mm Klarity™ composite 89dB 30-150W 102dB 8Ω compatible 5Ω 45Hz-20kHz 40Hz	2.5-way floorstanding speaker Bass reflex 25mm textile dome 150mm Klarity™ composite 150mm Klarity™ composite 89dB 30-200W 102dB 8Ω compatible 5Ω 40Hz-20kHz 35Hz	2-way centre speaker Closed-box system 25mm textile dome 130mm Klarity™ composite (x2) N/A 90dB 20-120W 96dB 8Ω compatible 4Ω 90Hz-20kHz 80Hz

w wharfedale

British loudspeakers have always enjoyed an excellent reputation around the world, and Wharfedale is perhaps the most famous brand of all. Stretching back to 1932, when Wharfedale's founder Gilbert Briggs built his first speaker in the cellar of his Yorkshire home, Wharfedale has been responsible for some of the most important loudspeakers ever produced, introducing many techniques and technologies that became commonplace such as the two-way loudspeaker (invented in 1945) and the use of ceramic magnets (pioneered in 1962). Now in its 88th year, Wharfedale continues its quest to deliver excellent sound quality and value for money with a wide range of class-leading speakers, including the latest iteration of the famous Diamond line – the classic entry point to high-fidelity sound.

www.wharfedale.co.uk



For more information and high res images please contact Tim Bowern T: 020 8654 8945 M: 07854 966071 E: tim@hashstar.co.uk